









UC ultrasuede® ambience

Style 862



3891 Aztec

**ULTRASUEDE® AMBIANCE:
BEAUTY MEETS PERFORMANCE**

Ultrasuede® Ambiance combines the aesthetic appeal of the finest suede with the performance of the most advanced ultra-microfiber.

Engineered to meet the most demanding specifications, Ultrasuede® Ambiance is as easy-care as it is versatile. No wonder designers and manufacturers in so many industries—from high-end contract installations and exclusive residential furnishings to first-class aviation, luxury marine and RV interiors—insist on Ultrasuede® Ambiance.

- Ideal for upholstery, wallcovering and a host of other applications
- Superior performance for fashion accessories, footwear, consumer electronics and more
- Soft, plush suede hand
- Soothing to the touch in any climate
- Excellent colorfastness
- Resists sagging, crocking, pilling and shrinking
- Highly abrasion-resistant—exceeds 200,000 Wyzenbeek double rubs
- Spot-cleanable and washable
- Unsurpassed range of today's most sought-after colors

CARE INSTRUCTIONS

Everyday Upkeep

A quick once-over with a lint brush will restore the sensuous nap and soft luster of Ultrasuede®. Periodically, it's also a good idea to vacuum the fabric and then dust it gently but thoroughly with a well-wrung damp white cloth or sponge.

Spot Cleaning

Gently pat spills with a paper towel until absorbed. For dried-in soiling, lightly brush or vacuum the stained area. If this doesn't work, try wiping the stained area from the outside in with a well-wrung white cloth dampened in lukewarm water.

Oil-Based Stains

Try to wipe up oily stains as much as possible—without spreading the stain—with a dry cloth or paper towel. Then, pat the stained area with a white cloth soaked in ethyl alcohol from the outside in, and pat the loosened dirt and oil off with a dry cloth. Repeat if necessary.

Old or Stubborn Stains

Try the spot-cleaning treatment described above; even non-water-soluble stains often require subsequent treatment with water. If staining persists, try treating with ethyl alcohol.

Caution: Never pour a cleaning product directly onto Ultrasuede®. Also avoid wiping with colored cloths as they may transfer dye.

Visit www.ultrasuede.com/about/care for more detailed instructions.

SPECIFICATIONS

Style:	862
Width:	55"
Put-up:	33 yard R.O.T.
Weight:	Approx. 11.1 oz. per square yard/ 17 oz. per linear yard
Thickness:	1 millimeter
Fiber Fineness:	0.19 denier
Composition:	80% polyester ultra-microfiber, non-woven with 20% non-fibrous polyurethane binder
CHARACTERISTICS	MEETS OR EXCEEDS
Abrasion:	ASTM D 3597 (7.4) Wyzenbeek—200,000 double rubs
Air Permeability:	ASTM D 737
F/R Rating:	CA Bulletin-117—Class I CA 133 Proto criteria B ASTM E84 Class A UFAC—Class I Rating Can be treated to meet FMVSS302 specifications
Pilling Resistance:	ASTM D 3512-96
Tensile Strength:	ASTM D 5034-95
Tear Strength:	ASTM D 5733-95
Dimensional Stability:	ASTM D 3597-95a (7.5)
Colorfastness to Crocking:	AATCC 8 Wet Procedure—Class 5.0 Dry Procedure—Class 5.0
Colorfastness to Light:	AATCC 16H—Class 5.0
Acoustical:	ASTM C 423-02